



Nominal Voltage Of Supply System V AC 230/400 230/400 Rated Insulation Voltage V AC 250 400 250 400 Polluti Jul 1th, 2024Relays RJ Series RJ Series — General Purpose Relays0.1  
1 12 100 10 1 250V AC 30V DC 1000 Load Current (A) X 10,000 Operations 0.1 1 8 100 10 1 1000 250V AC 30V DC RJ RJ1S RJ2S Maximum Switching Capacity Dimensions Dimensions  
Are In Mm. DC Resistive AC Resistive 1 10 100 1 0.1 10 250 12 Load Voltage (V) Load Current (A) DC Resistive 8 AC Resistive 1 10 100 1 Mar 3th, 2024Automotive Relays High  
Voltage Precharge RelaysAcc. IEC 60664-1 (2007) For Overvoltage Category I, Pollution Degree 2 Max. Altitude9) 5500m Other Data Compliant Flammability Of Plastic Material Acc.  
UL94-HB Ambient Temperature Range -40°C To +85°C Climatic Cycling With Condensation EN ISO Apr 3th, 2024.  
General Purpose Relays Industrial Relays Potter & Brum Eld ...VAC VAC ±15% VA 6 6 5.1 10.5 1.2 12 12 10.2 43 1.2 2424 20.41.25 160 4848 40.81.2 668 120 120 102.0 3900 1.35  
240 240 204.0 12000 1.5 All Gures Are Given For Coil Without Preenergization, At Ambient Temperature +23°C. Insulation Data In May 2th, 202420 Relays Contactors 10 Relays &  
ContactorsAC120V 120 VAC Coil Voltage AC240V 240 VAC Coil Voltage DC12V 12 VDC Coil Voltage DC24V 24 VDC Coil Voltage MODEL DESCRIPTION RH1B Relay, SPDT, Blade (use  
SH1B-05 Socket) RH2B Relay, DPDT, Blade (use SH2B-05 Socket) RH3B Relay, 3PDT, Blade (use SH3B-05 Socket) RH4B Relay, 4PDT, Blade (use Jan 3th, 2024General Purpose Relays  
Industrial Relays Potter & Brumfield24 24 18.0 472 1.25 48 48 36.0 1800 1.3 110 110 82.5 10000 1.25 4 Pole 5 5 3.75 14 1.8 6 6 4.5 20 1.8 12 12 9.0 80 1.8 24 24 18.0 320 1.8 48 48  
36.0 1250 1.85 110 110 82.5 6720 1.8 All Figures Are Given For Coil Without Preenergization, At Ambient Temperature +23°C.AgCdO, 1, 2 And 3 Pole Coil Versions, AC Coil Feb 3th,  
2024.  
RR Series Relays RR Series — General Purpose Power Relays1,500V AC, 1 Minute Between Contact Circuits: 1,500V AC, 1 Minute (1,000V AC Between NO-NC Contacts) Blade (RR1BA,  
RR2BA, RR3B) Between Live And Dead Parts: 2,000V AC, 1 Minute Between Contact Circuit And Operating Coil: 2,000V AC, 1 Minute Between Contact Circuits: 2,000V AC, 1 Minute  
Between Contacts Of Same Polarity: 1,000V AC, 1 Minute Feb 1th, 2024

There is a lot of books, user manual, or guidebook that related to Mercedes Benz Soft Top Relays PDF in the link below:

[SearchBook\[MTMvMzU\]](#)